







**ELC-LMT360-W-ARGB** 

**ELC-LMT240-W-ARGB** 








- The luminous addressable RGB fan and Aurabelt™ water block design
- Central Coolant Inlet (CCI) combined with patented Shunt-Chanel Technology (SCT) design
- Exclusive dual-convex blades

## **Features**


- Show your own uniqueness
  - The luminous addressable RGB fan and Aurabelt™ water block
  - 2 ways to control RGB lighting effects
  - White AIO CPU cooler
- Enhanced cooling performance
  - The combination of dual-chamber pump and CCI plus SCT technology
  - Dual Chamber water block design (patented)
  - Central Coolant Inlet (CCI) design combined with patented Shunt-Chanel Technology (SCT) cold plate
  - Exclusive dual-convex blades
- More durable and stable
  - Anti-vibration rubber pad on four-side fan frame
- User-friendly and compatibility
  - 400 mm weaved tubing
  - All-in-one bracket plate




Dual Chamber water block design (patented)



Central Coolant Inlet (CCI) design combined with patented Shunt-Chanel Technology (SCT) cold plate



Exclusive dual-convex blades



Anti-vibration rubber pad on four-side fan frame



The Aurabelt™ water block with 16.8 million color options









Through Motherboard Software



By Included ENERMAX RGB controller (\* only available for ELC-LMT360-W-ARGB)

## Dimension





**ELC-LMT360-W-ARGB** 

**ELC-LMT240-W-ARGB** 

## Specifications

CPU Socket         Intel® LGA 1700/1200/115x/2066/2011/2011-3/1366 AMD® AM5/AM4/AM3+/FM2+/FM1           Material         Copper Base with Aluminum Radiator           Radiator         394 x 120 x 27 mm         274 x 120 x 27 mm	
Radiator 394 x 120 x 27 mm 274 x 120 x 27 mm	
Bearing Ceramic Bearing	
MTBF 50,000 hrs	
Pump Motor Speed 3100 RPM ± 10%	
Rated Voltage 12V	
Water Rated Current - Pump [or 0.53A if not connected to 3 pin ARGB connector (5V/D/-/G	5)]
Block Rated Current - RGB LED 0.18A	
Tube Material Rubber	
Tube Length 400 mm	
Weight (W/O fan) 968 g 795 g	
Dimension 120 x 120 x 25 mm	
MTTF ≥ 50,000 hr	
Speed 500-1600 rpm	
Rated Voltage 12V	
Rated Current-Fan 0.17A	
Fan Rated Voltage - RGB LED 5V	
Rated Current - RGB LED 0.36A	
Air Flow 22.5~72.1 CFM	
Static Pressure 0.2~1.98 mm-H2O	
Noise Level 14~27 dBA	
Connector  4 pin PWM conntector 3 pin ARGB connector (5V/D/-/G)	
Accessory RGB Controller Yes No	
Thermal Grease Dow Corning® TC-5121C	
Logistic information	
Bar code EAN 4713157725387 4713157726056	
UPC 819315025383 819315026052	
Box dimension 448 x 205 x 137 mm 322 x 205 x 137 mm	
Gross Weight / unit 2.192 kg 1.75 kg	
Carton dimension 467x 292x 440 mm 435 x 338 x 440 mm	
Q'ty / carton 4pcs 6pcs	
Gross Weight / carton 9.788 kg 11.65 kg	